T5 High Output Energy Advantage

F54T5/841/HO/EA/ALTO 49W 40/1

Philips Energy Advantage T5 HO 49W lamps are environmentally-responsible, ultra-slim and have extraordinary light output with increased energy savings.

Product data

- General Information

Cap-Base	Miniature Bipin [Miniature Bipin]
Life To 50% Failures	30000 h
Preheat (Nom)	
Features	HO EA [High Output Energy Advantage]

- Light Technical

Color Code	841 [CCT of 4100K]
Initial lumen (Nom)	5000 lm
Luminous Flux (Rated) (Nom)	4450 lm
Color Designation	Cool White (CW)
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	102 lm/W
Chromaticity Coordinate X (Nom)	380
Chromaticity Coordinate Y (Nom)	380
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	93 lm/W
Color Rendering Index (Max)	85
Color Rendering Index (Min)	80
Color Rendering Index (Nom)	82

- Operating and Electrical

Power (Rated) (Nom)	48.0 W
Lamp Current (Nom)	0.460 A

- Temperature

Design Temperature (Nom)	35 °C

- Controls and Dimming

Dimmable	Yes

- Approval and Application

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	1.4 mg

- Product Data

Order product name	F54T5 841 HO EA ALTO 49W
EAN/UPC - Product	046677220525
Order code	220525
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927991984031
Net Weight (Piece)	104.500 g

PHILIPS

Dimensional drawing



G5, T5



TL5 HO Eco F54T5/841 HO EA 49W

Product	D	A	B	B	C
F54T5 841 HO EA ALTO 49W	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm

Photometric data





© 2015 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 10
data subject to change