



Ceramalux Non-ALTO

C50S68/M 12pk

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

• General Information

Cap-Base	Medium [Medium]
Operating Position	Universal [Universal]
Main Application	General Lighting (G)
Ansi Code	S68

• Light Technical

Initial lumen (Min)	3550 lm
Initial lumen (Nom)	4000 lm
Design Mean Lumens	3600 lm
Chromaticity Coordinate X (Nom)	540
Chromaticity Coordinate Y (Nom)	415
Correlated Color Temperature (Nom)	1900 K
Luminous Efficacy (rated) (Min)	71 lm/W
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	21

• Operating and Electrical

Power (Rated) (Nom)	50 W
Lamp Current (Nom)	1.18 A
Ignition Supply Voltage (Max)	110 V
Re-Ignition Time (Min) (Max)	2 min
Ignition Time (Max)	5 s

Voltage (Max)	62 V
Voltage (Min)	46 V
Voltage (Nom)	52 V

• Mechanical and Housing

Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass

• Approval and Application

Mercury (Hg) Content (Max)	17.7 mg
----------------------------	---------

• Luminaire Design Requirements

Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	190 °C

• Product Data


Order product name	C50S68/M 12pk
EAN/UPC - Product	046677409807
Order code	409805
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601144912
Net Weight (Piece)	0.010 kg

PHILIPS

Dimensional drawing

HPS R 50W E26 BD17 U

Product	D	C
C50S68/M 12pk	2.125 in	5.438 in



E26, BD-17



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 10
data subject to change