



Ceramalux ALTO

C70S62/ALTO 12PK

These lamps pass the EPA's TCLP test for non-hazardous materials. Ideal for industrial applications, warehouses, post top applications and parking lots.

Product data

• General Information

Cap-Base	Mogul [Mogul]
Operating Position	Universal [Universal]
Main Application	General and Street Lighting
Ansi Code HID	S62
Features	ALTO® (ALTO)

• Light Technical

Initial lumen (Min)	6100 lm
Initial lumen (Nom)	6800 lm
Design Mean Lumens	5670 lm
Chromaticity Coordinate X (Nom)	522
Chromaticity Coordinate Y (Nom)	425
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (rated) (Min)	87.4 lm/W
Luminous Efficacy (rated) (Nom)	97 lm/W
Color Rendering Index (Nom)	21

• Operating and Electrical

Power (Rated) (Nom)	70 W
Lamp Current (Nom)	1.6 A
Ignition Supply Voltage (Max)	110 V
Re-Ignition Time (Min) (Max)	2 min

Ignition Time (Max)	5 s
Voltage (Max)	60 V
Voltage (Min)	44 V
Voltage (Nom)	52 V

• Mechanical and Housing

Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass

• Approval and Application

Mercury (Hg) Content (Max)	17 mg
----------------------------	-------

• Luminaire Design Requirements

Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	210 °C

• Product Data

Order product name	SON 70W E39 ED75 CL SLV/12
EAN/UPC - Product	046677368692
Order code	368696
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601139901
Net Weight (Piece)	0.123 kg


PHILIPS

Dimensional drawing


HPS 70W E39 ED23 1/2 U ALTO

Product

SON 70W E39 ED75 CL.SLV/12



E39, ED-23 1/2



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 10
data subject to change