GE Lighting

97612 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

F26DBX/835/ECO4P

Product Photo

GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogrm per mean lm hr	115.3
Primary Application	Facilities
	Retail Display
	Hospitality
	Office
	Restaurant
	Warehouse
Product Technology	Compact Fluorescent
Base	G24q-3
Bulb Shape	G25

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	1530 lm
Nominal Initial Lumen per Watt	69
Initial Lumens-nominal	1800 lm
Color Rendering Index-CRI	82
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	97612
Description	F26DBX/835/ECO4P
Alternative Unit Of Measure	BUNDLE
Standard Package Quantity	50
Ean UPC	043168976121
Standard Package GTIN	
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
Sales Unit	Unit
UCC	043168976121

DIMENSIONS

Base Face to Top of Lamp	5.8 in
Nominal Length	6.4 in
Bulb Max Overall Length-MOL	6.4 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	100 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	26 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).