PHILIPS

LED

Lamps with
warm glow effect

The comfort of **softer and appealing light** with warm glow

Warm Glow
Dimmable Light

LED

Philips LED Lamps with warm glow effect

Create a warm, relaxing ambiance using Philips LED lamps with warm glow effect. Cutting-edge technology reduces the lamp's color temperature to a warm glow when dimmed, taking LED lamp dimming to new levels.

LED benefits with the ambiance of incandescent

- Traditional lamp shape
- A19, R20, BR30 and BR40 are ENERGY STAR® certified
- Color temperature ranges from 2700K to 2200K as the lamps are dimmed
- 25,000 hour ENERGY STAR® qualified life
- Smooth dimming to <10%
- A19 features all-around light*
- For warranty information visit www.philips.com/warranties

Easy to experience

- Incandescent-like dimming experience
- Long Life, can reduce maintenance costs
- Enjoy the energy-savings of LEDs without sacrificing light quality
- Dims to a smooth, even glow**

See footnotes on page three.

Philips LED Lamps with warm glow effect

Ordering, Electrical and Technical Data (Subject to change without notice)

Product Number	Model Number	Order Code	Nom. Watts	Volts	Description	Lamp Type	Base	Rated Avg. Life (Hrs.)[1]	Approx. Lumens	CRI	Color Temp. (K)	MOL (in.)
Standard Incandescent A19 40W ENERGY STAR® Equivalent[2]												
■ 45331-6	9290011176	6.5A19/2200-2700 DIM	6.5	120V	A19 Dimmable	A19	Med.	25,000	450	80	2700-2200	4.3
Standard Incandescent A19 60W ENERGY STAR® Equivalent[2]												
■ 45582-4	9290011345	9.5A19/LED/827-22 DIM	9.5	120V	A19 Dimmable	A19	Med.	25,000	800	80	2700-2200	4.3
Standard Incandescent BR/R 65W/45W ENERGY STAR® Equivalent[2]												
■ 45697-9	9290011557	6R20/LED/827-22/DIM	6	120V	R20 Flood Dimmable	R20	Med.	25,000	450	80	2700 - 2200	3.97
■ 45704-4	9290011555	9BR30/LED/827-22/DIM	9	120V	BR30 Flood Dimmable	BR30	Med.	25,000	650	80	2700 - 2200	5.20
■ 45701-0	9290011558	9BR40/LED/827-22/DIM	9	120V	BR40 Flood Dimmable	BR40	Med.	25,000	650	80	2700 - 2200	6.38
Standard Halogen MR16 35W ENERGY STAR® Equivalent[2]												
45453-8	9290011278	6.5MR16/F25/2700-2200 DIM	6.5	12V	MR16 Flood 25˚ Dimmable	MR16	GU5.3	25,000	410	80	2700-2200	1.9
45454-6	9290011279	6.5MR16/F35/2700-2200 DIM	6.5	12V	MR16 Flood 35˚ Dimmable	MR16	GU5.3	25,000	410	80	2700-2200	1.9
Standard Halogen PAR16 50W ENERGY STAR® Equivalent[2]												
□ 45765-5	9290011565	4.5GU10/LED/827-22/F25 DIM	4.5	120V	PAR16 Flood 25˚ Dimmable	PAR16	GU10	25,000	400	80	2700-2200	2.3

Shipping Data (Subject to change without notice)

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. Ft.)	Pallet Qty	SKUs per Layer	Layers High	SKU Dimensions (W x D x H) (In.)	Case Dimensions (W x D x H) (In.)	Pallet Dimensions (W x D x H) (In.)
Standard Incandescent A19 40W ENERGY STAR® Equivalent											
45331-6	45331-2	45331-7	6	1.19	0.13	1584	264	6	2.4 x 2.4 x 4.9	7.7 x 5.3 x 5.5	47.2 x 39.4 x 38.8
Standard Incandescent A19 60W ENERGY STAR® Equivalent											
45332-4	45332-9	45332-4	6	1.19	0.13	1584	264	6	2.4 x 2.4 x 4.9	7.7 x 5.3 x 5.5	47.2 x 39.4 x 38.8
Standard Incandescent BR/R 65W/45W ENERGY STAR® Equivalent[2]											
456979	456979	456974	6	0.82	0.114	2340	234	10	2.4 x 2.4 x 3.9	8.1 x 5.4 x 4.5	48 x 40 x 45.9
457044	457044	457049	6	2.79	0.31	840	120	7	3.6 x 3.6 x 5.2	11.4 x 7.8 x 6	48 x 40 x 42.8
457010	457013	457018	6	3.26	0.57	432	72	6	4.6 x 4.6 x 6.3	14.4 x 9.8 x 7	48 x 40 x 42.8
Standard Halogen MR16 35W ENERGY STAR® Equivalent											
45453-8	45453-1	45453-6	10	0.61	0.104	6110	470	13	1.77 x 1.77 x 2.17	9.3 x 4.0 x 2.8	47.2 x 39.4 x 42.6
45454-6	45454-8	45454-3	10	0.61	0.104	6110	470	13	1.77 x 1.77 x 2.17	9.3 x 4.0 x 2.8	47.2 x 39.4 x 42.6
Standard Halogen PAR16 50W ENERGY STAR® Equivalent											
45765-5	45765-5	45765-0	10	1.5	0.08	4560	380	12	2.0 x 2.0 x 2.4	10.5 x 4.4 x. 3.0	47.2 x 39.4 x 42.3

1. Rated average life based on engineering testing and probability analysis.
2. All Philips LED Lamp equivalencies for light output are based upon the ENERGY STAR guidelines as detailed in the ENERGY STAR Lamps V1.1 September 2014 specification.

■ This lamp is ENERGY STAR® Certified.
□ ENERGY STAR® Test in progress.
Light dims to a warm glow, similar to incandescent.

Footnotes from page 2:

* This lamp provides a measured light distribution of 310º. In use, this lamp gives the appearance of light all-around (360º).

** Dimmable when using leading and trailing edge dimmers. (See http://www.philips.com/ledtechguide for compatible dimmers.)

WARNINGS AND CAUTIONS
- Suitable for use in damp locations.
- Do not use in outdoor fixtures.
- Not for use in totally enclosed luminaires.
- Before replacing, turn off power and let lamp cool to avoid electrical shock or burn.

CAUTION: Risk of electric shock— do not use where directly exposed to water.

NOTES: These lamps comply with Part 15 of the FCC Rules. Operation is subject to the following 2 conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. This class B digital apparatus complies with Canadian ICES-003.

LISTED
LED LAMPS 3 PRR E335104

©2015 Koninklijke Philips N.V. All rights reserved.
Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

PLt-1523BN 08/15 philips.com

Philips Lighting, North America Corporation
200 Franklin Square Drive, Somerset, NJ 08873
Tel. 855-486-2216

Philips Lighting Canada Ltd.
281 Hillmount Rd, Markham, ON, Canada L6C 2S3
Tel. 800-668-9008