PL-L Long 4-Pin Base

PL-L 18W/835/4P

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes,configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum effciency and sleek design solutions are required.

Product data

- General Information

Cap-Base	2G11 [2G11]
Life To 50% Failures (Nom)	15000 h
Life To 50% Failures Preheat (Nom)	20000 h

- Light Technical

Color Code	835 [CCT of 3500K]
Initial lumen (Nom)	1200 lm
Color Designation	White (WH)
Lumen Maintenance 10000 h (Nom)	92 %
Lumen Maintenance 2000 h (Nom)	94 %
Lumen Maintenance 5000 h (Nom)	93 %
Chromaticity Coordinate X (Nom)	410
Chromaticity Coordinate Y (Nom)	395
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	82

- Operating and Electrical

Power (Rated) (Nom)	18.0 W
Lamp Current (Nom)	0.375 A
Voltage (Nom)	58 V

- Controls and Dimming

Dimmable	Yes

- Mechanical and Housing

Bulb Finish	Silicon
Cap-Base Information	4P

- Product Data

Order product name	PL-L 18W/835/4P
EAN/UPC - Product	046677359324
Order code	359323
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927903183521
Net Weight (Piece)	60.900 g
ILCOS Code	FSD-18/35/1B-E-2G11

PHILIPS

PL-L Long 4-Pin Base

Dimensional drawing



2G11, 4P



PL-L 18W/835/4P Silicon

Product	D	D1	C
PL-L 18W/835/4P	39.0 mm	18.0 mm	226.6 mm

Photometric data





© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 10
data subject to change