



Ceramalux Non-ALTO

C35S76/M 12PK

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

PHILIPS

Product data

• General Information

Cap-Base	Medium [Medium]
Operating Position	Universal [Universal]
Main Application	General Lighting (G)
ANSI Code HID	S76

• Light Technical

Luminous Flux (Rated) (Min)	2070 lm
Luminous Flux (Rated) (Nom)	2300 lm
Lumen Maintenance 10000 h (Nom)	93 %
Lumen Maintenance 20000 h	82 %
Design Mean Lumens	2025 lm
Chromaticity Coordinate X (Nom)	537
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (rated) (Min)	59 lm/W
Luminous Efficacy (rated) (Nom)	66 lm/W
Color Rendering Index (Nom)	21

• Operating and Electrical

Lamp Current (Nom)	0.83 A
Ignition Supply Voltage (Max)	110 V
Re-Ignition Time (Min) (Max)	5 min

Ignition Time (Max)	5 s
Voltage (Max)	62 V
Voltage (Min)	45 V
Voltage (Nom)	55 V

• Mechanical and Housing

Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass

• Approval and Application

Mercury (Hg) Content (Max)	31.9 mg
----------------------------	---------


• Luminaire Design Requirements

Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	190 °C

• Product Data

Order product name	C35S76/M 12PK
EAN/UPC - Product	046677409791
Order code	409797
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601144311
Net Weight (Piece)	0.010 kg

Dimensional drawing




E26, BD-17

HPS R 35W E26 BD17 U

Product	D	C
C35S76/M 12PK	2.125 in	5.438 in

Dimensional drawing



© 2015 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2015, December 10
data subject to change