GE Lighting

97599 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

F18DBX/830/ECO4P

Product Photo

GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogrm per mean lm hr	181.9
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	G24q-2
Bulb Shape	A19

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	970 lm
Nominal Initial Lumen per Watt	69
Initial Lumens-nominal	1250 lm
Color Rendering Index-CRI	82
Color Temperature	3000 K

PRODUCT INFORMATION

Product Code	97599
Description	F18DBX/830/ECO4P
Alternative Unit Of Measure	PACK

DIMENSIONS

Base Face to Top of Lamp	5.2 in
Nominal Length	5.8 in
Bulb Max Overall Length-MOL	5.8 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	65 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	18 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).