DencoSales
Your Source for Sign Supplies and Equipment

VOLTARC

TUFBEND® U-Lamps (6" Leg Spacing)

All TUFBEND® lamps ending in the suffix "CT" are specifically designed for use in cold temperature applications and will perform satisfactorily on existing ballasts at cold temperatures (<60°F). They are etched "for cold temperature use only".

Cool White Part #	Description	Day Light Part #	Description	DSN50 Part #	Description
13001	FTU6-24T12/CW/HO	13002	FTU6-24T12/D/HO	13003	FTU6-24T12/DSN50/HO
13004	FTU6-36T12/CW/HO	13005	FTU6-36T12/D/HO	13006	FTU6-36T12/DSN50/HO
13007	FTU6-48T12/CW/HO	13008	FTU6-48T12/D/HO	13009	FTU6-48T12/DSN50/HO
13010	FTU6-60T12/CW/HO	13011	FTU6-60T12/D/HO	13012	FTU6-60T12/DSN50/HO
13013	FTU6-72T12/CW/HO	13014	FTU6-72T12/D/HO	13015	FTU6-72T12/DSN50/HO
13016	FTU6-84T12/CW/HO	13017	FTU6-84T12/D/HO	13018	FTU6-84T12/DSN50/HO
13139	FTU6-96T12/CW/HO/CT	13138	FTU6-96T12/D/HO/CT	13021	FTU6-96T12/DSN50/HO/CT
13022	FTU6-120T12/CW/HO	13023	FTU6-120T12/D/HO	13024	FTU6-120T12/DSN50/HO

Lamp[2] Designation	Nominal Bent Length	Actual Bent Length to Socket	Lamp Watts	Rated[3] Life (hrs.)	Lumens[1] Cool White	Base	Mounts Rod	Shipping Weight per Case	Lamps per Case
FTU6-24T12/HO	12"	10 1/2"	36	9,000	1,600	FTU6/HO	FTU24	4	6
FTU6-36T12/HO	18"	16 1/2"	48	9,000	2,750	FTU6/HO	FTU36	6	6
FTU6-48T12/HO	24"	22 1/2"	60	12,000	4,000	FTU6/HO	FTU48	7	6
FTU6-60T12/HO	30"	28 1/2"	75	12,000	5,125	FTU6/HO	FTU60	10	6
FTU6-72T12/HO	36"	34 1/2"	87	12,000	6,125	FTU6/HO	FTU72	11	6
FTU6-84T12/HO	42"	40 1/2"	100	12,000	7,400	FTU6/HO	FTU84	12	6
FTU6-96T12/HO/CT	48"	46 1/2"	112	12,000	8,720	FTU6/HO	FTU96	14	6
FTU6-120T12/HO	60"	57"	132	12,000	10,650	FTU6/HO	FTU120	16	6

[1] Normal Lumen Rating: Daylight, 83% of Cool White, DSN50, 70% of Cool White. Ratings are approx. initial lumens at 100 hrs.

[2] Ballasts: U-Lamp ballasted same as corresponding straight lamps.

[3] Rated Life: The "rated life" of a statistically large group of lamps is defined as the time when 50% of the lamps have failed and 50% have survived. This is based on 3 hours of operation per start.