



T5 Preheat

F8T5/CW PH 25PK


Philips T5 Fluorescent Lamps are incredibly powerful, environmentally responsible, long life lamps with an ultra-slim profile. This translates into reduced maintenance and disposal costs and also allows the use of smaller fixtures—which reduces ceiling clutter.

Product data

General Information		Lamp Current (Nom)		Voltage (Nom)	
Cap-Base	G5 [G5]		0.145 A		56 V
Bulb Shape	T5 [16 mm (T5)]	Controls and Dimming			
Life To 10% Failures (Nom)	5000 h	Dimmable	Yes		
Life To 50% Failures (Nom)	10000 h	Approval and Application			
Life To 50% Failures Preheat (Nom)	10000 h	Energy Efficiency Label (EEL)	A		
System Description	na [-]	Mercury (Hg) Content (Nom)	4.4 mg		
Light Technical		Energy Consumption kWh/1000 h	8 kWh		
Color Code	33-640	Product Data			
Initial lumen (Nom)	410 lm	Order product name	F8T5/CW PH 25PK		
Color Designation	Cool White (CW)	EAN/UPC - Product	046677114640		
Lumen Maintenance 10000 h (Nom)	58 %	Order code	332478		
Lumen Maintenance 2000 h (Nom)	80 %	Numerator - Quantity Per Pack	1		
Lumen Maintenance 5000 h (Nom)	70 %	Numerator - Packs per outer box	25		
Chromaticity Coordinate X (Nom)	377	Material Nr. (12NC)	928001003321		
Chromaticity Coordinate Y (Nom)	381	Net Weight (Plece)	27.000 g		
Correlated Color Temperature (Nom)	4100 K	ILCOS Code	FD-8/41/2B-E-G5		
Luminous Efficacy (rated) (Nom)	51 lm/W				
Color Rendering Index (Nom)	60				
Operating and Electrical					
Power (Rated) (Nom)	7.1 W				

T5 Preheat

Dimensional drawing



Product	D	A	B	B	C
F8T5/CW PH 25PK	16 mm	288.3 mm	295.4 mm	293.0 mm	302.5 mm

TL Mini 8W/33-640

