PHILIPS

Lighting

T5 Preheat

F13T5/CW PH 25PK

Philips T5 Fluorescent Lamps are incredibly powerful, environmentally responsible, long life lamps with an ultra-slim profile. This translates into reduced maintenance and disposal costs and also allows the use of smaller fixtures—which reduces ceiling clutter.

Product data

General Information	
Cap-Base	G5 [G5]
Bulb Shape	T5 [16 mm (T5)]
Life To 10% Failures (Nom)	4000 h
Life To 50% Failures (Nom)	8000 h
Life To 50% Failures Preheat (Nom)	8000 h
System Description	na [-]

Light Technical	
Color Code	33-640
Initial lumen (Nom)	930 lm
Color Designation	Cool White (CW)
Lumen Maintenance 10000 h (Nom)	58 %
Lumen Maintenance 2000 h (Nom)	85 %
Lumen Maintenance 5000 h (Nom)	70 %
Chromaticity Coordinate X (Nom)	377
Chromaticity Coordinate Y (Nom)	381
Correlated Color Temperature (Nom)	4100 K
Luminous Efficacy (rated) (Nom)	71 lm/W
Color Rendering Index (Nom)	60

Operating and Electrical	
Power (Rated) (Nom)	13.0 W
Lamp Current (Nom)	0.170 A
Voltage (Nom)	90 V

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label (EEL)	A
Mercury (Hg) Content (Nom)	4.4 mg
Energy Consumption kWh/1000 h	14 kWh

Product Data	
Order product name	F13T5/CW PH 25PK
EAN/UPC - Product	046677115142
Order code	332536
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	928001503332
Net Weight (Piece)	40.200 g
ILCOS Code	FD-13/41/2B-E-G5

T5 Preheat

Dimensional drawing



Product	D	A	B	B	C
F13T5/CW PH 25PK	16 mm	516.9 mm	524.0 mm	521.6 mm	531.1 mm

TL Mini 13W/33-640

© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.