

T5 High Output

F54T5/850/HO/ALTO 40PK

Philips T5 HO lamps are environmentally-responsible, ultra-slim and have extraordinary light output and longer life.

Product data

General Information		Color Rendering Index (Min)	
Cap-Base	G5 [G5]	Color Rendering Index (Nom)	80
Bulb Shape	T5 [16 mm (T5)]	LLMF 2000 h Rated	96 %
Life To 50% Failures Preheat (Nom)	30000 h	LLMF 4000 h Rated	95 %
Features	HO Alto® [High Output Alto]	LLMF 6000 h Rated	94 %
System Description	High Output (HO)	LLMF 8000 h Rated	93 %
LSF Preheat 2000 h Rated	99 %	LLMF 12000 h Rated	92 %
LSF Preheat 4000 h Rated	99 %	LLMF 16000 h Rated	91 %
LSF Preheat 6000 h Rated	99 %	LLMF 20000 h Rated	90 %
LSF Preheat 8000 h Rated	99 %		
LSF Preheat 16000 h Rated	97 %		
LSF Preheat 20000 h Rated	84 %		
Light Technical		Operating and Electrical	
Color Code	850 [CCT of 5000K (2)]	Power (Rated) (Nom)	54.1 W
Initial lumen (Nom)	4800 lm	Lamp Current (Nom)	0.455 A
Luminous Flux (Rated) (Nom)	4275 lm		
Color Designation	Daylight	Temperature	
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	89 lm/W	Design Temperature (Nom)	35 °C
Chromaticity Coordinate X (Nom)	346		
Chromaticity Coordinate Y (Nom)	359	Controls and Dimming	
Correlated Color Temperature (Nom)	5000 K	Dimmable	Yes
Luminous Efficacy (rated) (Nom)	79 lm/W		
Color Rendering Index (Max)	85	Mechanical and Housing	
		Cap-Base Information	Green [Green Cap]

T5 High Output

Approval and Application


Energy Efficiency Label (EEL)	B
Mercury (Hg) Content (Nom)	1.4 mg

Product Data

Order product name	F54T5/850/HO/ALTO 40PK
EAN/UPC - Product	046677135102
Order code	135103

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927993185022
Net Weight (Piece)	105.000 g
ILCOS Code	FDH-54/50/1B-L/P-G5-16/1150

Dimensional drawing



Product	D	A	B	B	C
F54T5/850/HO/ALTO 40PK	17 mm	1149.0 mm	1156.1 mm	1153.7 mm	1163.2 mm

TL5 HO F54T5/850 HO Alto

