T8

9.9T8/COR/48-840/MF16/G 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.

Product data

General Information	
Base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
Technical Type	9.9-32W

Light Technical	
Color Code	841 [CCT of 4100K (841)]
Beam Angle (Nom)	240 °
Initial lumen (Nom)	1650 lm
Luminous Flux (Rated) (Nom)	1650 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	166.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	9.9 W
Lamp Current (Max)	100 mA
Lamp Current (Min)	43 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
UL Type	Type B - bypass the ballast
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V

Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	70 °C

T8

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Product Length	1200 mm

Approval and Application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate

Product Data	
Order product name	9.9T8/COR/48-840/MF16/G 10/1

EAN/UPC - Product	046677557430
Order code	557439
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002326004
Net Weight (Piece)	0.240 kg
Model Number	9290023260

Dimensional drawing

Product	D1	D2	A1	A2	A3
9.9T8/COR/48-840/MF16/G 10/1	25.7 mm	28 mm	1198 mm	1205 mm	1212 mm

TLED T8 120-277V 9.9-32W 1650lm 4000K

Photometric data



LEDtube 9,9W G13



LEDtube 9,9W G13 840

Photometric data



LEDtube 9,9W G13 840

Lifetime



LEDtube 50K-LED



LEDtube 50K FailureRate-LED



LEDtube 9,9W G13 LumenVsTc



LEDtube 50K-LMP

T8

Lifetime



LEDtube 50K LifetimeVsTc-LED

© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.